

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/22/2015

Reviewed on 03/22/2015

### \* 1 Identification

- **Product identifier**
- **Trade name: Architectural Lime Putty**
- **Relevant identified uses of the substance or mixture and uses advised against**  
No further relevant information available.
- **Details of the supplier of the safety data sheet**
- **Manufacturer/Supplier:**  
Lancaster Lime Works, LLC  
P.O. Box 266  
Bausman, PA 17504  
717.207.7014  
717.209.7116  
www.lancasterlimeworks.com
- **Emergency telephone number:**  
Chemtrec 1-800-424-9300 or outside USA 1-703-527-3887  
717-572-3715

### 2 Hazard(s) identification

- **Classification of the substance or mixture**



GHS05 Corrosion

Skin Corr. 1A H314 Causes severe skin burns and eye damage.

Eye Dam. 1 H318 Causes serious eye damage.

- **Label elements**
- **GHS label elements**  
The product is classified and labeled according to the Globally Harmonized System (GHS).
- **Hazard pictograms**



GHS05

- **Signal word** Danger
- **Hazard-determining components of labeling:**  
Calcium hydroxide
- **Hazard statements**  
Causes severe skin burns and eye damage.
- **Precautionary statements**  
Do not breathe dusts or mists.  
Wear eye protection / face protection.  
Wash thoroughly after handling.  
IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
Immediately call a poison center/doctor.  
Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).  
IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
Wash contaminated clothing before reuse.

(Contd. on page 2)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/22/2015

Reviewed on 03/22/2015

### Trade name: Architectural Lime Putty

If swallowed: Rinse mouth. Do NOT induce vomiting.  
Store locked up.  
Dispose of contents/container in accordance with local/regional/national/international regulations.

· **Unknown acute toxicity:**

50 percent of the mixture consists of ingredient(s) of unknown toxicity.

· **Classification system:**

· **NFPA ratings (scale 0 - 4)**



· **HMS-ratings (scale 0 - 4)**

HEALTH	4	Health = 4
FIRE	0	Fire = 0
REACTIVITY	0	Reactivity = 0

· **Other hazards** None known

### \* 3 Composition/information on ingredients

CAS: 7732-18-5 RTECS: ZC 0110000	water, distilled, conductivity or of similar purity	50%
-------------------------------------	---	-----

· **Chemical characterization: Mixtures**

· **Description:** Mixture of substances listed below with nonhazardous additions.

· **Dangerous Components:**

CAS: 1305-62-0 RTECS: EW 2800000	Calcium hydroxide ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302	50%
-------------------------------------	--	-----

### 4 First-aid measures

· **Description of first aid measures**

- **General information:** Immediately remove any clothing soiled by the product.
- **After inhalation:** In case of unconsciousness, place patient securely on side position for transportation.
- **After skin contact:** Immediately wash with water and soap and rinse thoroughly.
- **After eye contact:** Rinse opened eye for several minutes under running water. Then consult a doctor.
- **After swallowing:** Drink copious amounts of water and provide fresh air. Immediately call a doctor.
- **Information for doctor:**
- **Most important symptoms and effects, both acute and delayed** No further relevant information available.
- **Indication of any immediate medical attention and special treatment needed**  
No further relevant information available.

### 5 Fire-fighting measures

· **Extinguishing media**

· **Suitable extinguishing agents:**

CO<sub>2</sub>, extinguishing powder or water spray. Fight larger fires with water spray or alcohol resistant foam.

· **Special hazards arising from the substance or mixture** No further relevant information available.

· **Advice for firefighters**

· **Protective equipment:**

As in any fire, wear self-contained breathing apparatus pressure-demand (NIOSH approved or equivalent), and full protective gear to prevent contact with skin and eyes.

(Contd. on page 3)



# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/22/2015

Reviewed on 03/22/2015

**Trade name: Architectural Lime Putty**

## 6 Accidental release measures

- **Personal precautions, protective equipment and emergency procedures**  
Wear protective equipment. Keep unprotected persons away.
- **Environmental precautions:**  
Dilute with plenty of water.  
Do not allow to enter sewers/ surface or ground water.
- **Methods and material for containment and cleaning up:**  
Absorb with liquid-binding material (ie. sand, diatomite, acid binders, universal binders, sawdust).  
Use neutralizing agent.  
Dispose contaminated material as waste according to section 13.  
Ensure adequate ventilation.  
Dispose of the collected material according to regulations.
- **Reference to other sections**  
See Section 7 for information on safe handling.  
See Section 8 for information on personal protection equipment.  
See Section 13 for disposal information.

## 7 Handling and storage

- **Handling:**
- **Precautions for safe handling**  
Ensure good ventilation/exhaustion at the workplace.  
Prevent formation of aerosols.
- **Information about protection against explosions and fires:** No special measures required.
- **Conditions for safe storage, including any incompatibilities**
- **Storage:**
- **Requirements to be met by storerooms and receptacles:** No special requirements.
- **Information about storage in one common storage facility:** Not required.
- **Further information about storage conditions:** Keep receptacle tightly sealed.
- **Specific end use(s)** No further relevant information available.

## 8 Exposure controls/personal protection

- **Additional information about design of technical systems:** No further data; see section 7.
- **Control parameters**

<b>Components with occupational exposure limits:</b>	
<b>1305-62-0 Calcium hydroxide</b>	
PEL	Long-term value: 15* 5** mg/m <sup>3</sup> *total dust **respirable fraction
REL	Long-term value: 5 mg/m <sup>3</sup>
TLV	Long-term value: 5 mg/m <sup>3</sup>

- **Additional information:** The lists that were valid during the creation were used as basis.
- **Exposure controls**
- **Personal protective equipment:**
- **General protective and hygienic measures:**  
The usual precautionary measures for handling chemicals should be followed.  
Keep away from foodstuffs, beverages and feed.  
Immediately remove all soiled and contaminated clothing and wash before reuse.  
Wash hands before breaks and at the end of work.

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/22/2015

Reviewed on 03/22/2015

**Trade name: Architectural Lime Putty**

- Avoid contact with the eyes.
- Avoid contact with the eyes and skin.
- **Breathing equipment:** Not required.
- **Protection of hands:**



Protective gloves

The glove material has to be impermeable and resistant to the product/ the substance/ the preparation. Due to missing tests no recommendation to the glove material can be given for the product/ the preparation/ the chemical mixture.

Select glove material based on penetration times, rates of diffusion and degradation.

- **Material of gloves**

The selection of the suitable gloves does not only depend on the material, but also on further marks of quality and varies from manufacturer to manufacturer. As the product is a preparation of several substances, the resistance of the glove material can not be calculated in advance and has therefore to be checked prior to the application.

- **Penetration time of glove material**

The exact break-through time has to be determined and observed by the manufacturer of the protective gloves.

- **Eye protection:** Tightly sealed goggles

### 9 Physical and chemical properties

- **Information on basic physical and chemical properties**

- **General Information**

- **Appearance:**

**Form:** Solid moist material

**Color:** White

- **Odor:** Odorless

- **Odor threshold:** Not determined.

- **pH-value:** Not determined.

- **Change in condition**

**Melting point/Melting range:** Not determined.

**Boiling point/Boiling range:** 100 °C (212 °F)

- **Flash point:** Not applicable.

- **Flammability (solid, gaseous):** Not applicable.

- **Ignition temperature:**

**Decomposition temperature:** Not determined.

- **Auto igniting:** Product is not self-igniting.

- **Danger of explosion:** Product does not present an explosion hazard.

- **Explosion limits:**

**Lower:** 0.0 Vol %

**Upper:** 0.0 Vol %

- **Vapor pressure @ 20 °C (68 °F):** 23 hPa (17 mm Hg)

- **Density @ 20 °C (68 °F):** 1.62 g/cm<sup>3</sup> (13.519 lbs/gal)

- **Relative density** Not determined.



# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/22/2015

Reviewed on 03/22/2015

**Trade name: Architectural Lime Putty**

- **Vapor density** Not determined.
- **Evaporation rate** Not determined.
- **Solubility in / Miscibility with Water:** Fully miscible.
- **Partition coefficient (n-octanol/water):** Not determined.
- **Viscosity:**
  - Dynamic:** Not determined.
  - Kinematic:** Not determined.
- **Solvent content:**
  - Organic solvents:** 0.0 %
  - Water:** 50.0 %
- **Solids content:** 50.0 %
- **Other information** No further relevant information available.

## 10 Stability and reactivity

- **Reactivity** No further relevant information available.
- **Chemical stability** Stable under normal conditions.
- **Thermal decomposition / conditions to be avoided:** No decomposition if used according to specifications.
- **Possibility of hazardous reactions** No dangerous reactions known.
- **Conditions to avoid** No further relevant information available.
- **Incompatible materials:** No further relevant information available.
- **Hazardous decomposition products:** No dangerous decomposition products known.

## 11 Toxicological information

- **Information on toxicological effects**
- **Acute toxicity:**

· <b>LD/LC50 values that are relevant for classification:</b>		
<b>1305-62-0 Calcium hydroxide</b>		
Oral	LD50	7340 mg/kg (rat)

- **Primary irritant effect:**
- **on the skin:** Strong caustic effect on skin and mucous membranes.
- **on the eye:**
  - Strong irritant with the danger of severe eye injury.
  - Corrosive effect.
  - Causes serious eye irritation.
- **Additional toxicological information:**
  - The product shows the following dangers according to internally approved calculation methods for preparations:
  - Corrosive
  - Irritant
  - Swallowing will lead to a corrosive effect on mouth and throat and to the danger of perforation of esophagus and stomach.

(Contd. on page 6)



# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/22/2015

Reviewed on 03/22/2015

**Trade name: Architectural Lime Putty**

· **Carcinogenic categories**

· <b>IARC (International Agency for Research on Cancer)</b>
Group 1 - Carcinogenic to humans Group 2A - Probably carcinogenic to humans Group 2B - Possibly carcinogenic to humans Group 3 - Not classifiable as to its carcinogenicity to humans Group 4 - Probably not carcinogenic to humans
· <b>NTP (National Toxicology Program)</b>
None of the ingredients are listed.
· <b>OSHA-Ca (Occupational Safety &amp; Health Administration)</b>
None of the ingredients are listed.

## 12 Ecological information

- **Toxicity**
- **Aquatic toxicity:** No further relevant information available.
- **Persistence and degradability** No further relevant information available.
- **Behavior in environmental systems:**
- **Bioaccumulative potential** No further relevant information available.
- **Mobility in soil** No further relevant information available.
- **Additional ecological information:**
- **General notes:** Must not reach bodies of water or drainage ditch undiluted or unneutralized.
- **Results of PBT and vPvB assessment**
- **PBT:** Not applicable.
- **vPvB:** Not applicable.
- **Other adverse effects** No further relevant information available.

## 13 Disposal considerations

- **Waste treatment methods**
- **Recommendation:**  
Must not be disposed of together with household garbage. Do not allow product to reach sewage system.
- **Uncleaned packagings:**
- **Recommendation:** Disposal must be made according to official regulations.
- **Recommended cleansing agent:** Water, if necessary with cleansing agents.

## 14 Transport information

- **UN-Number**
- **DOT, ADR, IMDG, IATA** UN1760
- **UN proper shipping name**
- **DOT** Corrosive liquids, n.o.s. (Calcium hydroxide)
- **ADR** UN1760 Corrosive liquids, n.o.s. (Calcium hydroxide)
- **IMDG, IATA** CORROSIVE LIQUID, N.O.S. (Calcium hydroxide)

(Contd. on page 7)

## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/22/2015

Reviewed on 03/22/2015

**Trade name: Architectural Lime Putty**

· **Transport hazard class(es)**

· **DOT**



· **Class** 8 Corrosive substances  
· **Label** 8

· **ADR**



· **Class** 8 (C9) Corrosive substances  
· **Label** 8

· **IMDG, IATA**



· **Class** 8 Corrosive substances  
· **Label** 8  
· **Packing group**  
· **DOT, ADR, IMDG, IATA** III  
· **Environmental hazards:** Not applicable.  
· **Special precautions for user** Warning: Corrosive substances  
· **Danger code (Kemler):** 80  
· **EMS Number:** F-A,S-B  
· **Segregation groups** Alkalis  
· **Transport in bulk according to Annex II of MARPOL73/78 and the IBC Code** Not applicable.  
· **Transport/Additional information:**  
· **DOT**  
· **Quantity limitations** On passenger aircraft/rail: 5 L  
On cargo aircraft only: 60 L

· **ADR**

· **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **IMDG**

· **Limited quantities (LQ)** 5L  
· **Excepted quantities (EQ)** Code: E1  
Maximum net quantity per inner packaging: 30 ml  
Maximum net quantity per outer packaging: 1000 ml

· **UN "Model Regulation":** UN1760, Corrosive liquids, n.o.s. (Calcium hydroxide), 8, III

(Contd. on page 8)



## Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/22/2015

Reviewed on 03/22/2015

**Trade name: Architectural Lime Putty**

### 15 Regulatory information

- **Safety, health and environmental regulations/legislation specific for the substance or mixture**
- **Sara**

- **Section 355 (extremely hazardous substances):**

None of the ingredients are listed.

- **Section 313 (Specific toxic chemical listings):**

None of the ingredients are listed.

- **TSCA (Toxic Substances Control Act):**

All ingredients are listed.

- **Proposition 65**

- **Chemicals known to cause cancer:**

None of the ingredients are listed.

- **Chemicals known to cause reproductive toxicity for females:**

None of the ingredients are listed.

- **Chemicals known to cause reproductive toxicity for males:**

None of the ingredients are listed.

- **Chemicals known to cause developmental toxicity:**

None of the ingredients are listed.

- **Carcinogenic categories**

- **EPA (Environmental Protection Agency)**

None of the ingredients are listed.

- **TLV (Threshold Limit Value established by ACGIH)**

None of the ingredients are listed.

- **NIOSH-Ca (National Institute for Occupational Safety and Health)**

None of the ingredients are listed.

- **GHS label elements**

The product is classified and labeled according to the Globally Harmonized System (GHS).

- **Hazard pictograms**



GHS05

- **Signal word** Danger

- **Hazard-determining components of labeling:**

Calcium hydroxide

- **Hazard statements**

Causes severe skin burns and eye damage.

- **Precautionary statements**

Do not breathe dusts or mists.

Wear eye protection / face protection.

Wash thoroughly after handling.

(Contd. on page 9)





# Safety Data Sheet (SDS)

OSHA HazCom Standard 29 CFR 1910.1200(g) and GHS Rev 03.

Printing date 03/22/2015

Reviewed on 03/22/2015

## Trade name: Architectural Lime Putty

IF ON SKIN (or hair): Remove/Take off immediately all contaminated clothing. Rinse skin with water/shower.  
 If in eyes: Rinse cautiously with water for several minutes. Remove contact lenses, if present and easy to do. Continue rinsing.  
 Immediately call a poison center/doctor.  
 Specific treatment (see supplementary first aid instructions on this Safety Data Sheet).  
 IF INHALED: Remove victim to fresh air and keep at rest in a position comfortable for breathing.  
 Wash contaminated clothing before reuse.  
 If swallowed: Rinse mouth. Do NOT induce vomiting.  
 Store locked up.  
 Dispose of contents/container in accordance with local/regional/national/international regulations.

**National regulations:**

The product is subject to be labeled according with the prevailing version of the regulations on hazardous substances.

**State Right to Know**

CAS: 1305-62-0 RTECS: EW 2800000	Calcium hydroxide ⚠ Skin Corr. 1A, H314; Eye Dam. 1, H318; ⚠ Acute Tox. 4, H302	25-50%
CAS: 7732-18-5 RTECS: ZC 0110000	water, distilled, conductivity or of similar purity	25-50%

All ingredients are listed.

**Chemical safety assessment:** A Chemical Safety Assessment has not been carried out.

## 16 Other information

The information and recommendations in this safety data sheet are, to the best of our knowledge, accurate as of the date of issue. Nothing herein shall be deemed to create warranty, expressed or implied and shall not establish a legally valid contractual relationship. It is the responsibility of the user to determine applicability of this information and the suitability of the material or product for any particular purpose.

**Date of preparation / last revision** 03/22/2015 / 1

**Abbreviations and acronyms:**

- ADR: The European Agreement concerning the International Carriage of Dangerous Goods by Road
- ADN: The European Agreement concerning the International Carriage of Dangerous Goods by Inland Waterways
- IMDG: International Maritime Code for Dangerous Goods
- DOT: US Department of Transportation
- IATA: International Air Transport Association
- ACGIH: American Conference of Governmental Industrial Hygienists
- EINECS: European Inventory of Existing Commercial Chemical Substances
- ELINCS: European List of Notified Chemical Substances
- CAS: Chemical Abstracts Service (division of the American Chemical Society)
- NFPA: National Fire Protection Association (USA)
- HMIS: Hazardous Materials Identification System (USA)
- LC50: Lethal concentration, 50 percent
- LD50: Lethal dose, 50 percent
- Acute Tox. 4: Acute toxicity, Hazard Category 4
- Skin Corr. 1A: Skin corrosion/irritation, Hazard Category 1A
- Eye Dam. 1: Serious eye damage/eye irritation, Hazard Category 1

**\* Data compared to the previous version altered.**

SDS created by MSDS Authoring Services [www.msdsauthoring.com](http://www.msdsauthoring.com) (877) 204-9106